



Sustainable Solutions for Health, Productivity and the Environment.



# Thermo Gloss Plus

UHS Floor Finish/Sealer



# Thermo Gloss Plus

## Where to Use

Thermo Gloss Plus is a high solids, dry bright floor finish. Thermo Gloss Plus provides an instant brilliant gloss that becomes deeper and tougher each time it is burnished using a 1,500 RPM+ burnisher. When used according to directions, Thermo Gloss Plus is suitable for use on vinyl, vinyl asbestos, linoleum, asphalt, rubber or terrazzo floors. Thermo Gloss Plus is the perfect choice to be used when only the highest levels of appearance will do. More durable and scuff resistant than other “burnishable” finishes, Thermo Gloss Plus provides brilliant gloss and tough protection 24 hours a day.

## Benefits

- Burnishes to a brilliant gloss “wet look”.
- Becomes more durable each time it’s burnished.
- Detergent resistant.
- Meets slip resistant standard ASTM D-2047.
- Excellent leveling characteristics.
- Easy to maintain.
- Provides excellent gloss retention.
- Recommended for frequent burnishing programs

## Directions for Use

For best results, begin with a properly prepared floor.

1. Remove all old finish with RMC Ultra Strip or Super Strip, diluted according to directions, or, if stripping is unnecessary, scrub thoroughly with Hi Con or DfE 401 to remove all surface soil.
2. After stripping, rinse with clear water and allow to dry.
3. Apply Thermo Gloss Plus in a thin or moderate even coat, allowing adequate dry time between coats (30-45 minutes minimum, longer in humid conditions).

## Routine Maintenance:



To obtain optimum results with the RMC Ultra High Speed Floor Care System, proper floor maintenance procedures are a must.

Dust mop the floor and carefully remove sticky residue with a scraper.

1. Dust mop the floor and carefully remove any remaining foreign materials with a scraper or putty knife.
2. Damp mop or autoscrob the floor with Thermo Clean or Perfect 7 (mixed 1 oz. per gallon of water) to remove surface soil. Use blue, red or white pads on the auto scrubber, based on the degree of soil. Allow to dry.
3. Burnish with an Ultra High Speed Floor Machine equipped with a hair blend pad or synthetic pad with similar characteristics.
4. To enhance gloss even further and lengthen time between recoating, apply RMC Ultra Restore, following label directions, prior to burnishing.

## Distributor Contact Info

Properties	
Color	Opaque white
Fragrance	Mild
Viscosity	<10
VOC's (EPA Method 24 % by weight)	5.6-6.0
pH	9
Total Solids	25%
Coverage per gallon (3.8 Litres)	2000ft <sup>2</sup> (185m <sup>2</sup> )

Available Package Sizes	Package Code	
55 gallon drum	#11848757 	
5 gallon pail	#11848745 	

For handling and precautionary information, reference the product label and safety data sheet.

For more information about RMC call 1.800.836.1633 or go to [www.rochestermidland.com](http://www.rochestermidland.com)